

MANNINGTON COMMERCIAL

CONSTRUCTION SPECIFICATIONS

Infinity™ Six Foot

| | |
|-----------------------|----------------------------------------------|
| PRIMARY SUBSTRATE: | 100% Synthetic |
| PRECOAT LAYER: | 100% Vinyl Non-Aqueous Polymer |
| FIRST LAYER: | 100% Vinyl With Recycled Content |
| STABILIZING MEMBRANE: | Non-woven Fiberglass |
| SECOND LAYER: | 100% Vinyl With Recycled Content |
| BACKING STRUCTURE: | Closed Cell |
| TOTAL BACKING WEIGHT: | 105 ounces per square yard (style dependent) |

PERFORMANCE SPECIFICATIONS

| | |
|-----------------------------------------|----------------------------|
| METHENAMINE PILL TEST: (FF 1-70) | PASSES |
| RADIANT PANEL TEST: (ASTM E-648) | CLASS I |
| NBS SMOKE TEST: (ASTM E-662) | 450 OR LESS (FLAMING MODE) |
| INDOOR AIR QUALITY: (EPA Protocol) | MEETS CRI GREEN LABEL PLUS |
| DIMENSIONAL STABILITY: (AACHEN TEST) | PASSES |
| MOISTURE IMPACT TEST: | PASSES |
| WARRANTY: | LIMITED LIFETIME WARRANTY |