

**DESCRIPTION**

Mannington Commercial's MT-711 adhesive is pressure sensitive, solvent free, and acrylic based. It is nonflammable, and anti-microbial with zero calculated VOC's. Refer to Mannington Professional Installation Guide.

**FEATURES**

- Easy application
- VOC-compliant / solvent-free / low odor
- Non-flammable
- Moisture and alkali resistant
- Readily identifiable mylar chips
- Contains fungicide protection
- Complies with SCAQMD Rule 1168

**DIRECTIONS**

- Make sure the underfloor is clean and free of all foreign matter such as dirt, paint, oil, wax, old adhesives, etc. It must be smooth and level.
- The building must have permanent heat / air.
- Sand off any high spots and fill low spots with the appropriate Mannington patching compound. Keep the adhesive, floor covering and jobsite at a minimum of 70°F for at least 48 hours before, during, and after the installation.
- Always check cartons to assure the pattern number is correct and that the shade and lot numbers are the same on all cartons. To minimize shade variation, mix and install tiles from several different cartons.
- Apply MT-711 with a trowel notched 1/16" wide, 1/32" deep, and 1/32" apart in an even and uniform thickness. The adhesive must be spread over 100% of the exposed subfloor, leaving no gaps or puddles. Uniform coverage can be maintained by keeping the trowel clean and properly notched.
- After spreading, let the adhesive dry. Normal drying time is approximately 15-40 minutes. High humidity and lower temperatures may extend that time. For best results and a long lasting bond: **Do not allow the MT-711 adhesive to dry completely. Adhesive must be "tacky" enough to transfer to the modular backing.**
- When placing tiles, set them firmly against adjoining tiles and press into the adhesive. Do not slide tiles into place.
- You can remove fresh adhesive with water. Dried adhesive can be removed with mineral spirits.

**COVERAGE**

Approximately 250-300 sq ft per gallon.

**PACKAGING**

1-Gallon Pail #849889, weighs approximately 9 lbs (4.08 kg) 4 per carton  
4-Gallon Pail # 849886, weighs approximately 37 lbs (16.33 kg)

**PRECAUTIONS**

- Use with adequate ventilation.
- Do not use where **excessive** moisture, alkali, or hydrostatic pressure exists.
- Do not apply directly over gypsum-based surfaces.
- Prevent prolonged breathing of vapor and skin contact.
- Do not ingest.
- Avoid contact with eyes.
- **KEEP OUT OF THE REACH OF CHILDREN.**